



---

## YOUR BUSINESS NEEDS A TRUCK YOU CAN RELY ON

---

When you need a truck that gets the job done and is always ready for the next one, a truck that leaves worry behind, the International® DuraStar® is a no-brainer.

DuraStar is available with a strong range of diesel engine options – including the Cummins® ISB6.7, Cummins ISL9 and the durable Navistar® N9 – in several horsepower and torque ranges.

DuraStar features the Diamond Logic® electrical system bringing the brainpower, flexibility and convenience of advanced electronics to the truck's electrical system, making the vehicle easier to use and maintain.

DuraStar is a hard-working, versatile truck that will help you get the most out of your business.



**DURA**Star®

DURASTAR®



## INTERNATIONAL \* DURA STAR \* SPECIFICATIONS

### GVW

- ▶ 23,500 – 44,600 lbs.

### Models/BBC/BA

- ▶ 4300, 4400: 107" BBC, 40" BA

### Cab Configurations

- ▶ Day Cab
- ▶ Extended Cab
- ▶ Crew Cab

### Wheelbase Options

- ▶ 128" – 254"

### Axle Configurations

- ▶ 4x2, 6x4

### Rear Axle

#### SINGLE REAR AXLE (4x2)

- ▶ Meritor: 13,500 – 30,000 lbs.
- ▶ Dana Spicer: 13,500 – 30,000 lbs.

#### TANDEM REAR AXLE (6x4)

- ▶ Meritor: 34,000 – 40,000 lbs.
- ▶ Dana Spicer: 34,000 – 40,000 lbs.

### Front Axle

- ▶ Meritor: 8,000 – 14,600 lbs. (4x2, 6x4)
- ▶ Dana Spicer: 8,000 – 14,000 lbs.

### Frames

- ▶ High Strength Low-alloy Steel 50,000 – 80,000 PSI
- ▶ Heat Treated Alloy Steel 120,000 PSI (4x2 Mid Cab Tractor)
- ▶ Clean CA available for body mounting

### Front Suspension

- ▶ Spring Parabolic Taper Leaf: 8,000 – 14,600 lbs.

### Rear Suspension

- ▶ Spring Single Vari-Rate: 15,500 – 23,000 lbs.
- ▶ Tandem, 4-Spring Multileaf: 34,000 lbs. (6x4)
- ▶ IROS Air Suspension Available for Single and Tandem Axle

### Electrical System

- ▶ Diamond Logic® Electrical System

### ALTERNATORS

- ▶ 12 Volt 160 – 320 Amp.

### BATTERY SYSTEMS

- ▶ 12 Volt, 2 to 3 Batteries

### HEADLIGHTS

- ▶ Long Life Halogen

### Exhaust System

- ▶ Single, Horizontal, After-treatment Device Frame Mounted Right or Left Side, Back of Cab, Horizontal or Vertical Tailpipe
- ▶ Switchback After-treatment Device Mounted Right Side Under Cab, Horizontal or Vertical Tailpipe
- ▶ Horizontal After-treatment Device Mounted In-line, Back of Cab, Horizontal Tailpipe

### Brakes

- ▶ Hydraulic Disc with Four Channel ABS, Optional Traction Control
- ▶ Air Brakes with ABS, Optional Traction Control, Optional Electronic Stability Program with Traction Control

### Steering

- ▶ TRW/Ross Power
- ▶ Sheppard Power (4x2 Mid Cab Tractor, 6x4)

### Engines

- ▶ Cummins® ISB6.7: 200 hp, 520 lb.-ft. torque up to 325 hp, 750 lb.-ft. torque
- ▶ Navistar® N9: 275 hp, 860 lb.-ft. torque up to 330 hp, 950 lb.-ft. torque
- ▶ Cummins ISL9: Up to 350 hp, 1000 lb.-ft torque

### Transmissions

- ▶ Eaton® Fuller: 6, 10 Speed Manual
- ▶ Eaton: Procion™ 7 Speed Dual Clutch Automatic
- ▶ Allison: 1000, 2000, 3000 Series (HS, EVS, RDS) Automatic
- ▶ Allison: 3000 TRV Series Automatic

### Fuel Tank

- ▶ 40 – 140 Gallon Non-Polished and Polished Aluminum, Mounted Right Side, Left Side or Dual Under Cab

### Tires

- ▶ Continental, Michelin, Goodyear

### KEY FEATURES

- ▶ Set-back axle provides outstanding maneuverability and a tight turning radius, making it easier to negotiate through cramped spaces
- ▶ Diamond Logic® electrical system gives you diagnostic help and a standard convenience package with parking brake alarm and pre-trip exterior light checks, and easily integrates control of body and equipment mounted to the truck
- ▶ Optimized drive train performance matches transmission shift points with engine power curves for better responsiveness, reliability, and fuel economy
- ▶ A sloped hood and swept-back, curved windshield design offer a commanding view of the road
- ▶ OnCommand™ Connection, our industry leading remote diagnostics system monitors your fleet, alerts you to issues and provides action plans for repairs to help avoid unscheduled down time

**ALTRUCK**  
**INTERNATIONAL TRUCK CENTRES**



**WWW.ALTRUCK.COM**  
**888.539.7110**